



## DECLARATION OF CONFORMITY

The undersigned, representing the  
**Ture Johanssons Trävaru AB**  
and manufacturing plant  
**Klevshult**

herewith declares that the

### **Machine strength graded structural timber**

<b>Characteristic</b>	<b>Performance declaration</b>
Species/species group	WPPA: spruce ( <i>Picea abies</i> ) and pine ( <i>Pinus sylvestris</i> )
Growth area	NNE Europe (Northern and North Eastern Europe)
Range of thickness (fire resistance)	31 -110 mm
Range of width (fire resistance)	60 -300mm
Range of length	More than 2,0 m
Surface finish	Sawn or planed
Dry or wet graded	Dry graded
Grading machine	Dynagrade
Strength, stiffness and density	C30, C27, C24, C18 and C16; TR26; LS22, LS18, LS15 and LS11
Durability	4 (EN 350-2)
Reaction to fire	D-s2, d0 (EN 14081-1, Table C.1)
Release of dangerous substances	NPD

is in conformity with the provisions of the EC Directive 89/106/CEE (Construction Products Directive - CPD) when intended to be used for structural applications, and that Annex ZA of

### **EN 14081-1:2005+A1:2011**

has been applied.

The CE marking was first applied in 2008

The notified body SP Technical Research Institute of Sweden (Notified Body 0402) has issued the certificate of factory production control CPD – 27 42 02

Klevshult 2011-12-01

Kvalitetssystemansvarig

Peter Nilsson

Ture Johanssons Trävaru AB  
568 92 Skillingaryd  
Sweden